

OPTIMUM PROFESSIONAL TECHNICAL BULLETIN #104a

December 5, 2017

Opti-Coat Pro Plus Information and Application

Opti-Coat Pro Plus is an enhanced 2 step version of **Opti-Coat Pro**. The first step, **Opti-Coat Pro** is a ceramic clear coating warrantied for 5 years with superior resistance to scratching, chemical etching, fading due to UV, and provides outstanding release properties. **Opti-Coat Pro Plus** can be applied 30 minutes after **Opti-Coat Pro** with the same application method as **Opti-Coat Pro** using the same applicator, allowing the vehicle to be coated and driven the same day. When applied within the first 60 minutes, **Opti-Coat Pro Plus** permanently bonds to **Opti-Coat Pro** and adds great gloss and slickness for a fantastic shine that lasts for years. **Opti-Coat Pro Plus** increases the warranty protection to 7 years.

Package contains:

- 15 cc **Opti-Coat Pro**
- 2 oz **Opti-Coat Primer**
- 10 cc **Opti-Coat Pro Plus**
- Microfiber Towel
- Foam Applicator
- Warranty card
-

Directions for application:

1. Allow **Opti-Coat Pro** to cure for 30 minutes on panel prior to applying **Opti-Coat Pro Plus**.
2. Prime applicator by making an X pattern across the pad. Only a few drops will be needed for each subsequent panel.
3. Wipe **Opti-Coat Pro Plus** onto a single panel at a time in a thin layer using circular motions.
4. Once **Opti-Coat Pro Plus** is applied, inspect the panel with adequate lighting, looking for any high spots that have not completely cross linked away to clear.
5. Use applicator or included paint safe microfiber to even out any areas where you see streaks. This step is key as any spots not leveled will have to be polished if allowed to cure. Panels will feel a bit tacky and will be self-leveling during cure time so avoid any unnecessary touching, wiping or contact to produce best result
6. Repeat steps 2 - 5 for each panel where application is desired. Not recommended for glass.
7. Ideally keep the vehicle indoors for 12 hours or more prior to delivering to customer. If not possible, 1 hour or more after application of **Opti-Coat Pro Plus**, add **Opti-Seal** to the surface (do not use **Opti-Coat Hyper Seal** on a coated surface for a minimum of 7 days). Schedule a quality control/inspection wash with the customer in the 7-30 day period following the application.