



## Safety Data Sheet

### Opti-Coat Paint Guard

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System  
Date of Revision: 06/09/2023 Revision: 0

#### Section 1 - Chemical Product and Company Identification

1.1 Product Name: Opti-Coat Paint Guard

1.2 Synonym: Blend

1.3 Optimum Polymer Technologies, Inc., 5768 Distribution Drive, Memphis, TN 38141, 901.363.4955, Email: info@optimumcarcare.com

1.4 Recommended Use: Coating

1.5 RESTRICTIONS on USE None

1.6 Emergency Response Number: CHEMTREC 800-424-9300 US and Canada

International Emergency Telephone Number: +1-703-527-3887

1.7 24 Hour Emergency Assistance: 1-901-292-4324

#### Section 2 - Hazards Identification

### 2.1 GHS HAZARD

#### Hazard Classes

Combustible Liquid

Eye Irritation

Skin Irritation

Harmful to Aquatic Life long Lasting Effects

#### Hazard Categories

Category 4

Category 2A

Category 2

Category 3

2.2 Signal Word: Warning

2.3 Pictograms:



Irritant

# Opti-Coat Paint Guard

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

## 2.4 Hazard Statements

<b>PHYSICAL HAZARDS:</b>	<b>H227: Combustible Liquid.</b>
<b>HEALTH HAZARDS</b>	<b>H315: Causes skin irritation. H319: Causes serious eye irritation.</b>
<b>ENVIRONMENTAL HAZARDS:</b>	<b>H312: Harmful to aquatic life long-lasting effects.</b>
<b>PRECAUTIONARY STATEMENTS:</b>	<b>P102: Keep out of reach of children P210: Keep away from sparks and open flames- No smoking. P264: Wash hands thoroughly after handling. P273: Avoid release to the environment. P280: Wear protective gloves or eye protection.</b>
<b>RESPONSE STATEMENTS:</b>	<b>P302+P352: IF ON SKIN: Wash with plenty of water. P305+P351: IF IN EYES: Rinse cautiously with water for at least 15 minutes. If present, remove contact lenses if easy to do so. P313+P332+P337: If skin or eye irritation persists, get medical attention. P362+P364: Take off contaminated clothing and wash them before reuse. P370+P378: In case of fire, use foam, carbon dioxide, dry chemical to extinguish the fire.</b>
<b>STORAGE STATEMENTS:</b>	<b>P403+P235: Store in a well-ventilated place. Keep cool.</b>
<b>DISPOSAL STATEMENTS:</b>	<b>P501: Dispose of content and container following local, regional, national, or international regulations.</b>

**2.5** Hazards not otherwise classified (HNOC) or not covered by GHS: None

# Opti-Coat Paint Guard

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

## Section 3 - Composition / Information on Ingredients

### 3.1

CAS#	EC/ List #	Chemical Names	Percent	GHS Classification
541-02-6	208-764-9	Decamethylcyclopentasiloxane	80-84	Flam. Liq. 4, H227
25608-33-7	607-756-6	2-Propenoic acid, 2-methyl-, butyl ester, polymer with methyl 2-methyl-2-propenoate	5-10	Not Classified
63148-57-2	613-152-3	Siloxanes and Silicones, Me hydrogen	2-5	Not Classified
142-96-1	205-573-3	di- <i>n</i> -butyl ether dibutyl ether	2-3	Flam. Liq 3 H226, Skin Irrit.2 H315, Eye Irrit. 2 H319, Aquatic Chronic 3 H412
90387-00-1	631-462-7	Polysilazane	1-5	Skin Corr. 1B, Eye Dam. 1 H318
540-97-6	208-762-8	Dodecamethylcyclohexasiloxane	1-2	Not Classified

Note: No Fragrance Allergens in this blend.

**3.3 Trade Secret Provision and Chemical Concentration Disclosure:** Per OSHA and GHS Regulations, we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a range and apply to the hazards as identified in this Safety Data Sheet.

## Section 4 - First Aid Measures

**4.1 Eye:** Contact with the eyes can cause serious irritation. Symptoms may include discomfort or pain and redness.

**Eyes:** Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

**4.2 Skin:** Contact can cause skin irritation.

**Skin:** Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately and wash clothing before reuse.

# Opti-Coat Paint Guard

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

**4.3 Ingestion:** Causes headache, gastrointestinal pain, nausea.

**Ingestion:** Do NOT induce vomiting. Get medical aid immediately.

**4.4 Inhalation:** Can produce headaches, dizziness, nausea, and impaired vision.

**Inhalation:** Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

**4.5 After first aid, get appropriate paramedic, or community medical support.** The severity of outcome following exposure may be more related to the time between exposure and treatment, rather than the amount of the exposure. Therefore, there is a need for rapid treatment of any exposure.

**4.6 Note to Physicians:** If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment, we will immediately disclose the specific chemical identity. Call CHEMTREC 800-424-9300 or 703-527-3887. We will require a written statement of need and confidentiality agreement, per OSHA's Trade Secret Regulations as soon as circumstances permit. In non-emergency situations, we will, upon written request, disclose a specific chemical identity.

## Section 5 - Fire-Fighting Measures

**5.1 General Fire Hazards:** Use water to cool containers exposed to fire.

**5.2 Hazardous Combustion Products:** Avoid fumes of burning products.

**5.3 Extinguishing Media:** Carbon dioxide, dry chemical, foam.

**5.4 Fire Fighting Equipment/Instructions:** Firefighters should wear full-face, self-contained breathing apparatus, and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

## Section 6 - Accidental Release Measures

**6.1 Spill /Leak Procedures:** Avoid breathing vapors.

**6.2 Spills:** Contain and collect spillage with absorbent material such as sand, earth, vermiculite, or diatomaceous earth and place in a container for disposal.

## Section 7 - Handling and Storage

**7.1 Handling Precautions:** Wash hands and exposed skin thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Avoid ingestion and contact with eyes, skin, or clothing. Avoid inhalation.

**7.2 Storage Requirements:** Keep container tightly closed. Store locked up in a well-ventilated place.

# Opti-Coat Paint Guard

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

## Section 8 - Exposure Controls / Personal Protection

### 8.1

Chemical Names	ACGIH- TLV	OSHA – PEL	WEEL-PEL
Decamethylcyclopentasiloxane	Not Established	Not Established	10 ppm TWA
2-Propenoic acid, 2-methyl-, butyl ester, polymer with methyl 2-methyl-2-propenoate	50 ppm TWA	100 ppm TWA	
Siloxanes and Silicones, Me hydrogen	None Shown	None Shown	
di- <i>n</i> -butyl ether dibutyl ether	None Shown	None Shown	
Polysilazane	None Shown	None Shown	
Dodecamethylcyclohexasiloxane	None Shown	None Shown	

### 8.2

**ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value.**

**OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits.**

**NOTE: TWA Means** "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour workweek which shall not be exceeded.

**C Means:** Maximum allowable human exposure **limit** for an airborne or gaseous substance), which is not to be exceeded even momentarily.

**8.3 Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

**8.4 Contaminated Equipment:** Separate contaminated work clothes from street clothes and launder before reuse. Remove this material from your shoes and clean personal protective equipment.

### 8.5 Personal protective equipment

#### 8.5.1 Respiratory protection

Where risk assessment shows, air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied-air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### 8.5.2 Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Registered trademark of The Chemours Company FC, LLC.

# Opti-Coat Paint Guard

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

## 8.5.3 Eye protection

Safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

## 8.5.4 Skin and body protection

Impervious protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

## 8.6 Protective Clothing Pictograms



## Section 9 - Physical and Chemical Properties

### 9.1

**Physical State:** Liquid

**Appearance:** Clear

**Odor:** Mild

**Vapor Pressure:** Not Available

**Vapor Density (Air=1):** Not Available

**Specific Gravity (H<sub>2</sub>O=1,):** Not Available

**Relative Density:** Not Available

**Odor Threshold:** Not Available

**Flammability (solid, gas):** Not Applicable

**Evaporation rate:** Not Available

**Partition coefficient octanol/water:** Not Available

**Water Solubility:** 100%

**Flash Point:** 170 °F (77 °C)

**Boiling Point:** 410 °F (210 °C)

**Freezing/Melting Point:** Not Available

**LEL:** Not Available

**UEL:** Not Available

**Viscosity:** Not Available

**Autoignition Temperature:** Not Available

**Decomposition temperature:** Not Available

**pH:** Not Available

**Grams VOC less water:** Not Available

## Section 10 - Stability and Reactivity

**10.1 Stability:** Stable under ordinary conditions of use and storage.

**10.2 Polymerization:** Hazardous polymerization has not been reported.

**10.3 Chemical Incompatibilities:** Strong oxidizing agents.

**10.4 Hazardous Decomposition Products:** Carbon monoxide.

**10.5 Conditions to Avoid:** Avoid freezing.

## Section 11- Toxicological Information

### 11.1

Acute Toxicity Estimate for this blend (ATE)

ATE (Oral): >5000 mg/kg.

ATE (Dermal): >2000 mg/kg.

ATE (Inhalation vapor/mist): >20mg/l

# Opti-Coat Paint Guard

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

**11.1.1** OECD Guideline Test results found in the European Chemical Agency Data Base shows that no components of this product to cause Oral Toxicity.

**11.1.2** OECD Guideline Test results found in the European Chemical Agency Data Base shows that no components of this product to be Inhalation Toxicity.

**11.1.3** OECD Guideline Test results found in the European Chemical Agency Data Base shows that no components of this product to Dermal Toxicity.

**11.2** Route of Entry: Skin and Eye Contact

**11.3 Aspiration Hazard:** European Chemical Agency Data Base shows that no components of this product may be fatal if swallowed and enters airways.

**11.4 Mutagenicity:** OECD Guideline Test results found in the European Chemical Agency DataBase show no components of this product to cause genetic defects.

**11.5 Skin Corrosion/Irritation:** OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause skin irritation.

**11.6 Serious Eye Damage/Irritation:** OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause serious eye irritation.

**11.7 Reproductive toxicity:** OECD Guideline Test results found in the European Chemical Agency DataBase show no components of this product to cause damage to fertility or the unborn child.

**11.8 Skin Sensitization** OECD Guideline Tests results found in the European Chemical Agency DataBase show no components of this product to cause skin sensitivity.

**11.9 Respiratory Sensitization** OECD Guideline Tests results found in the European Chemical Agency DataBase show no components of this product to cause respiratory sensitivity.

**11.10 Specific Target Organ Toxicity (Single Exposure):** Skin and Eyes.

**11.11 Target Organ Toxicity (Repeated Exposure):** Skin and Eyes.

**11.12 Signs and Symptoms:** Include discomfort or pain and redness.

**11.13 Carcinogenicity:** OECD Guideline Test results found in the European Chemical Agency Data Base shows that no components of this product to cause cancer.

Chemical Name	IARC	ACGIH	NTP	OSHA
Decamethylcyclopentasiloxane	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%
2-Propenoic acid, 2-methyl-, butyl ester, polymer with methyl 2-methyl-2-propenoate	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%
Siloxanes and Silicones, Me hydrogen	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%

# Opti-Coat Paint Guard

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

di- <i>n</i> -butyl ether dibutyl ether	Not classifiable as to carcinogenicity to humans	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%
Polysilazane	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%
Dodecamethylcyclohexasiloxane	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%	No component of this product present at levels greater than or equal to 0.1%

## Section 12 - Ecological Information

### 12.1

Product Name	Results	Species	Exposure
Decamethylcyclopentasiloxane	LC50 500 mg/l	Fish	96 hours
2-Propenoic acid, 2-methyl-, butyl ester, polymer with methyl 2-methyl-2-propenoate	Expected to be harmful to aquatic organisms. May cause long-term adverse effects in the environment		
Siloxanes and Silicones, Me hydrogen	No data available		
di- <i>n</i> -butyl ether dibutyl ether	LC50 32.5 mg/l	Fish	96 hours
Polysilazane	LC50 52 mg/l	Fish	96 hours
Dodecamethylcyclohexasiloxane	None Shown		

**Toxicity:** OECD Guideline Test results found in the European Chemical Agency DataBase show components of this product to cause long-term harmful toxicity to aquatic life.

**12.2 Mobility:** Inconclusive technical data.

**12.3 Persistence/degradability:** Inconclusive technical data.

**12.4 Bioaccumulation:** Inconclusive technical data.

**12.5 Other adverse effects:** Inconclusive technical data.

## Section 13 - Disposal Considerations

**13.1 Disposal: DO NOT REUSE EMPTY CONTAINER!** The container should be emptied before discard. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

## Section 14 - Transport Information

### 14.1 US Transport Information

Not regulated

### 14.2 IMDG Transport Information

Not regulated



# Opti-Coat Paint Guard

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

## 14.3 UN Dangerous Goods Transport Information

Not regulated

## Section 15 - Regulatory Information

### 15.1 US Regulations

**US. Toxic Substances Control Act:** All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

**Toxic Release Inventory (TRI):** This product doesn't contain chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know- Act of 1986 (40 CFR 372).

**CERCLA Hazardous Substances and corresponding RQs:** None

**SARA Community Right-to-Know Program:** All components in this blend

**Clean Water Act:** None

**Clean Air Act:** None

**OSHA:** All ingredients are regulated by 29 CFR 1910.1200.

### State Regulations

**California prop. 65:** None

### Chemicals on the following State Right to Know Lists:

**Massachusetts:** All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements

**New Jersey** All components of this product are on the New Jersey inventory or are exempt from Inventory requirements

**Pennsylvania:** All components of this product) are on the Pennsylvania Inventory or are exempt from Inventory requirements.

### 15.4 International Regulations:

**Australian Inventory of Chemical Substances:** All components of this product are on the Inventory or are exempt from Inventory requirements.

**National Existing Chemical Inventory in Taiwan:** All components of this product are on the Inventory or are exempt from Inventory requirements.

**Philippine Inventory of Chemicals and Chemical Substances** All components of this product are on the Inventory or are exempt from Inventory requirements.

**China Existing Chemical Inventory:** All components of this product are on the Inventory or are exempt from Inventory requirements.

## Opti-Coat Paint Guard

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

### Section 16 - Other Information

**16.1 Disclaimer:** The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall make their determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

**16.2 References:** CHEMpendium database of the Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller online, European Chemical Agency Data Base, and MSDS and SDS of chemicals in this mixture.

**16.4 SDS Preparation Date** 06/09/2023

**SDS Previous Issue Date:** 07/17/2020

Prepared by SJC Compliance Education, Inc.

1319 Varese Dr.

Pearland, TX. 77581

[steve@sjcedu.org](mailto:steve@sjcedu.org)

