



Safety Data Sheet

Opti-Coat Pro

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Date of Revision: 06/09/2023 Revision: 0

Section 1 - Chemical Product and Company Identification

1.1 Product Name: Opti-Coat Pro

1.2 Synonym: Blend

1.3 Optimum Polymer Technologies, Inc., 5768 Distribution Drive, Memphis, TN 38141, 901.363.4955, Email: info@optimumcarcare.com

1.4 Recommended Use: Coating

1.5 RESTRICTIONS on USE None

1.6 Emergency Response Number: CHEMTREC 800-424-9300 US and Canada

International Emergency Telephone Number: +1-703-527-3887

1.7 24 Hour Emergency Assistance: 1-901-292-4324

Section 2 - Hazards Identification

2.1 GHS HAZARD

Hazard Classes

Combustible Liquid

Eye Irritation

Skin Irritation

Harmful to Aquatic Life long Lasting Effects

Hazard Categories

Category 4

Category 2A

Category 2

Category 3

2.2 Signal Word: Warning

2.3 Pictograms:



Irritant

Opti-Coat Pro

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

2.4 Hazard Statements

| | |
|----------------------------------|--|
| PHYSICAL HAZARDS: | H227: Combustible Liquid. |
| HEALTH HAZARDS | H315: Causes skin irritation. H319: Causes serious eye irritation. |
| ENVIRONMENTAL HAZARDS: | H312: Harmful to aquatic life long-lasting effects. |
| PRECAUTIONARY STATEMENTS: | P102: Keep out of reach of children P210: Keep away from sparks and open flames- No smoking. P264: Wash hands thoroughly after handling. P273: Avoid release to the environment. P280: Wear protective gloves or eye protection. |
| RESPONSE STATEMENTS: | P302+P352: IF ON SKIN: Wash with plenty of water. P305+P351: IF IN EYES: Rinse cautiously with water for at least 15 minutes. If present, remove contact lenses if easy to do so. P313+P332+P337: If skin or eye irritation persists, get medical attention. P362+P364: Take off contaminated clothing and wash them before reuse. P370+P378: In case of fire, use foam, carbon dioxide, dry chemical to extinguish the fire. |
| STORAGE STATEMENTS: | P403+P235: Store in a well-ventilated place. Keep cool. |
| DISPOSAL STATEMENTS: | P501: Dispose of content and container following local, regional, national, or international regulations. |

2.5 Hazards not otherwise classified (HNOC) or not covered by GHS: None

Opti-Coat Pro

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Section 3 - Composition / Information on Ingredients

3.1

| CAS# | EC/ List # | Chemical Names | Percent | GHS Classification |
|------------|------------|---|---------|--|
| 541-02-6 | 208-764-9 | Decamethylcyclopentasiloxane | 80-84 | Flam. Liq. 4, H227 |
| 25608-33-7 | 607-756-6 | 2-Propenoic acid, 2-methyl-, butyl ester, polymer with methyl 2-methyl-2-propenoate | 5-10 | Not Classified |
| 63148-57-2 | 613-152-3 | Siloxanes and Silicones, Me hydrogen | 2-5 | Not Classified |
| 142-96-1 | 205-573-3 | di- <i>n</i> -butyl ether dibutyl ether | 2-3 | Flam. Liq 3 H226, Skin Irrit.2 H315, Eye Irrit. 2 H319, Aquatic Chronic 3 H412 |
| 90387-00-1 | 631-462-7 | Polysilazane | 1-5 | Skin Corr. 1B, Eye Dam. 1 H318 |
| 540-97-6 | 208-762-8 | Dodecamethylcyclohexasiloxane | 1-2 | Not Classified |

Note: No Fragrance Allergens in this blend.

3.3 Trade Secret Provision and Chemical Concentration Disclosure: Per OSHA and GHS Regulations, we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a range and apply to the hazards as identified in this Safety Data Sheet.

Section 4 - First Aid Measures

4.1 Eye: Contact with the eyes can cause serious irritation. Symptoms may include discomfort or pain and redness.

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

4.2 Skin: Contact can cause skin irritation.

Skin: Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately and wash clothing before reuse.

Opti-Coat Pro

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

4.3 Ingestion: Causes headache, gastrointestinal pain, nausea.

Ingestion: Do NOT induce vomiting. Get medical aid immediately.

4.4 Inhalation: Can produce headaches, dizziness, nausea, and impaired vision.

Inhalation: Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

4.5 After first aid, get appropriate paramedic, or community medical support. The severity of outcome following exposure may be more related to the time between exposure and treatment, rather than the amount of the exposure. Therefore, there is a need for rapid treatment of any exposure.

4.6 Note to Physicians: If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment, we will immediately disclose the specific chemical identity. Call CHEMTREC 800-424-9300 or 703-527-3887. We will require a written statement of need and confidentiality agreement, per OSHA's Trade Secret Regulations as soon as circumstances permit. In non-emergency situations, we will, upon written request, disclose a specific chemical identity.

Section 5 - Fire-Fighting Measures

5.1 General Fire Hazards: Use water to cool containers exposed to fire.

5.2 Hazardous Combustion Products: Avoid fumes of burning products.

5.3 Extinguishing Media: Carbon dioxide, dry chemical, foam.

5.4 Fire Fighting Equipment/Instructions: Firefighters should wear full-face, self-contained breathing apparatus, and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

Section 6 - Accidental Release Measures

6.1 Spill /Leak Procedures: Avoid breathing vapors.

6.2 Spills: Contain and collect spillage with absorbent material such as sand, earth, vermiculite, or diatomaceous earth and place in a container for disposal.

Section 7 - Handling and Storage

7.1 Handling Precautions: Wash hands and exposed skin thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Avoid ingestion and contact with eyes, skin, or clothing. Avoid inhalation.

7.2 Storage Requirements: Keep container tightly closed. Store locked up in a well-ventilated place.

Opti-Coat Pro

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Section 8 - Exposure Controls / Personal Protection

8.1

| Chemical Names | ACGIH- TLV | OSHA – PEL | WEEL-PEL |
|---|-----------------|-----------------|------------|
| Decamethylcyclopentasiloxane | Not Established | Not Established | 10 ppm TWA |
| 2-Propenoic acid, 2-methyl-, butyl ester, polymer with methyl 2-methyl-2-propenoate | 50 ppm TWA | 100 ppm TWA | |
| Siloxanes and Silicones, Me hydrogen | None Shown | None Shown | |
| di- <i>n</i> -butyl ether dibutyl ether | None Shown | None Shown | |
| Polysilazane | None Shown | None Shown | |
| Dodecamethylcyclohexasiloxane | None Shown | None Shown | |

8.2

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value.

OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits.

NOTE: TWA Means "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour workweek which shall not be exceeded.

C Means: Maximum allowable human exposure **limit** for an airborne or gaseous substance), which is not to be exceeded even momentarily.

8.3 Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

8.4 Contaminated Equipment: Separate contaminated work clothes from street clothes and launder before reuse. Remove this material from your shoes and clean personal protective equipment.

8.5 Personal protective equipment

8.5.1 Respiratory protection

Where risk assessment shows, air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied-air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

8.5.2 Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Registered trademark of The Chemours Company FC, LLC.

Opti-Coat Pro

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

8.5.3 Eye protection

Safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

8.5.4 Skin and body protection

Impervious protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

8.6 Protective Clothing Pictograms



Section 9 - Physical and Chemical Properties

9.1

Physical State: Liquid

Appearance: Clear

Odor: Mild

Vapor Pressure: Not Available

Vapor Density (Air=1): Not Available

Specific Gravity (H₂O=1,): Not Available

Relative Density: Not Available

Odor Threshold: Not Available

Flammability (solid, gas): Not Applicable

Evaporation rate: Not Available

Partition coefficient octanol/water: Not Available

Water Solubility: 100%

Flash Point: 170 °F (77 °C)

Boiling Point: 410 °F (210 °C)

Freezing/Melting Point: Not Available

LEL: Not Available

UEL: Not Available

Viscosity: Not Available

Autoignition Temperature: Not Available

Decomposition temperature: Not Available

pH: Not Available

Grams VOC less water: Not Available

Section 10 - Stability and Reactivity

10.1 Stability: Stable under ordinary conditions of use and storage.

10.2 Polymerization: Hazardous polymerization has not been reported.

10.3 Chemical Incompatibilities: Strong oxidizing agents.

10.4 Hazardous Decomposition Products: Carbon monoxide.

10.5 Conditions to Avoid: Avoid freezing.

Section 11- Toxicological Information

11.1

Acute Toxicity Estimate for this blend (ATE)

ATE (Oral): >5000 mg/kg.

ATE (Dermal): >2000 mg/kg.

ATE (Inhalation vapor/mist): >20mg/l

Opti-Coat Pro

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

11.1.1 OECD Guideline Test results found in the European Chemical Agency Data Base shows that no components of this product to cause Oral Toxicity.

11.1.2 OECD Guideline Test results found in the European Chemical Agency Data Base shows that no components of this product to be Inhalation Toxicity.

11.1.3 OECD Guideline Test results found in the European Chemical Agency Data Base shows that no components of this product to Dermal Toxicity.

11.2 **Route of Entry:** Skin and Eye Contact

11.3 **Aspiration Hazard:** European Chemical Agency Data Base shows that no components of this product may be fatal if swallowed and enters airways.

11.4 **Mutagenicity:** OECD Guideline Test results found in the European Chemical Agency DataBase show no components of this product to cause genetic defects.

11.5 **Skin Corrosion/Irritation:** OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause skin irritation.

11.6 **Serious Eye Damage/Irritation:** OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause serious eye irritation.

11.7 **Reproductive toxicity:** OECD Guideline Test results found in the European Chemical Agency DataBase show no components of this product to cause damage to fertility or the unborn child.

11.8 **Skin Sensitization** OECD Guideline Tests results found in the European Chemical Agency DataBase show no components of this product to cause skin sensitivity.

11.9 **Respiratory Sensitization** OECD Guideline Tests results found in the European Chemical Agency DataBase show no components of this product to cause respiratory sensitivity.

11.10 **Specific Target Organ Toxicity (Single Exposure):** Skin and Eyes.

11.11 **Target Organ Toxicity (Repeated Exposure):** Skin and Eyes.

11.12 **Signs and Symptoms:** Include discomfort or pain and redness.

11.13 **Carcinogenicity:** OECD Guideline Test results found in the European Chemical Agency Data Base shows that no components of this product to cause cancer.

| Chemical Name | IARC | ACGIH | NTP | OSHA |
|---|--|--|--|--|
| Decamethylcyclopentasiloxane | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% |
| 2-Propenoic acid, 2-methyl-, butyl ester, polymer with methyl 2-methyl-2-propenoate | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% |
| Siloxanes and Silicones, Me hydrogen | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% |

Opti-Coat Pro

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

| | | | | |
|---|--|--|--|--|
| di- <i>n</i> -butyl ether dibutyl ether | Not classifiable as to carcinogenicity to humans | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% |
| Polysilazane | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% |
| Dodecamethylcyclohexasiloxane | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% | No component of this product present at levels greater than or equal to 0.1% |

Section 12 - Ecological Information

12.1

| Product Name | Results | Species | Exposure |
|---|---|---------|----------|
| Decamethylcyclopentasiloxane | LC50 500 mg/l | Fish | 96 hours |
| 2-Propenoic acid, 2-methyl-, butyl ester, polymer with methyl 2-methyl-2-propenoate | Expected to be harmful to aquatic organisms. May cause long-term adverse effects in the environment | | |
| Siloxanes and Silicones, Me hydrogen | No data available | | |
| di- <i>n</i> -butyl ether dibutyl ether | LC50 32.5 mg/l | Fish | 96 hours |
| Polysilazane | LC50 52 mg/l | Fish | 96 hours |
| Dodecamethylcyclohexasiloxane | None Shown | | |

Toxicity: OECD Guideline Test results found in the European Chemical Agency DataBase show components of this product to cause long-term harmful toxicity to aquatic life.

12.2 Mobility: Inconclusive technical data.

12.3 Persistence/degradability: Inconclusive technical data.

12.4 Bioaccumulation: Inconclusive technical data.

12.5 Other adverse effects: Inconclusive technical data.

Section 13 - Disposal Considerations

13.1 Disposal: DO NOT REUSE EMPTY CONTAINER! The container should be emptied before discard. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

Section 14 - Transport Information

14.1 US Transport Information

Not regulated

14.2 IMDG Transport Information

Not regulated

Opti-Coat Pro

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

14.3 UN Dangerous Goods Transport Information

Not regulated

Section 15 - Regulatory Information

15.1 US Regulations

US. Toxic Substances Control Act: All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

Toxic Release Inventory (TRI): This product doesn't contain chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know- Act of 1986 (40 CFR 372).

CERCLA Hazardous Substances and corresponding RQs: None

SARA Community Right-to-Know Program: All components in this blend

Clean Water Act: None

Clean Air Act: None

OSHA: All ingredients are regulated by 29 CFR 1910.1200.

State Regulations

California prop. 65: None

Chemicals on the following State Right to Know Lists:

Massachusetts: All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements

New Jersey All components of this product are on the New Jersey inventory or are exempt from Inventory requirements

Pennsylvania: All components of this product) are on the Pennsylvania Inventory or are exempt from Inventory requirements.

15.4 International Regulations:

Australian Inventory of Chemical Substances: All components of this product are on the Inventory or are exempt from Inventory requirements.

National Existing Chemical Inventory in Taiwan: All components of this product are on the Inventory or are exempt from Inventory requirements.

Philippine Inventory of Chemicals and Chemical Substances All components of this product are on the Inventory or are exempt from Inventory requirements.

China Existing Chemical Inventory: All components of this product are on the Inventory or are exempt from Inventory requirements.

Opti-Coat Pro

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Section 16 - Other Information

16.1 Disclaimer: The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall make their determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

16.2 References: CHEMpendium database of the Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller online, European Chemical Agency Data Base, and MSDS and SDS of chemicals in this mixture.

16.4 SDS Preparation Date 06/09/2023

SDS Previous Issue Date: 07/17/2020

Prepared by SJC Compliance Education, Inc.

1319 Varese Dr.

Pearland, TX. 77581

steve@sjcedu.org

